



Delock PCI Express x16 Card to 5 x internal M.2 Key B / SATA

Description


This PCI Express card by Delock expands the PC by five M.2 slots. Up to five M.2 SATA modules can be connected in format 2280, 2260, 2242, 2230 with this card.

SATA devices

Furthermore it is possible to connect up to five SATA devices to the card. Therefor the scope of delivery includes adapters and SATA cables. A combination of SATA devices and M.2 SSDs is also possible.

Low Profile Form Factor

By using the included low profile bracket, the PCI Express card can be also installed into a Mini-PC.



Item no. 90435

EAN: 4043619904358 Country of origin: China Package: Retail Box

Technical details

• Connectors:

internal:

5 x 67 pin M.2 key B slot

1 x PCI Express x16, V3.0

- Chipset: JMicron JMB585
- Interface: SATA
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.5 mm, application of doublesided assembled modules supported
- Data transfer rate up to 6 Gb/s
- 6 x LED indicator
- Supports Native Command Queuing (NCQ)
- Supports S.M.A.R.T.
- Supports TRIM
- Supports DevSleep
- Hot Swap
- Bootable



System requirements


- Linux Kernel 3.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express x16 / x32 slot

Package content

- PCI Express card
- · Low profile bracket
- 5 x M.2 to SATA adapter
- 5 x SATA cable, length ca. 50 cm
- Screwdriver
- · Mounting material
- User manual


Images













General

| Function: | bootable |
|---|---|
| Supported operating system: | Linux Kernel 3.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |
| LED indicator: | 6 x |
| Slot: | SATA |
| Supported module: | M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA |
| Maximum height of the components on the module: | 1.5 mm application of double-sided assembled modules supported |

Interface

| Internal: | 5 x SATA 6 Gb/s 7 pin plug |
|-----------|----------------------------|
| | 1 x PCI Express x16, V3.0 |
| | 5 x 67 pin M.2 key B slot |

Technical characteristics

| Chipset: | JMicron JMB585 |
|----------|----------------|
|----------|----------------|