

Delock USB Barcode Scanner 1D and 2D wired for stationary installation - German Version

Description

This stationary barcode scanner by Delock is ideal for **space-saving** installation in a table top and connection to the system. It is also ideal for use in access control, for example in a digitalised turnstile. All common **1D and 2D** barcode types can also be precisely captured from the smartphone.

Automatic adaptation to ambient brightness

The scanner automatically adapts to the ambient brightness and captures up to 60 scans per second under optimal lighting conditions. In low ambient brightness, the barcode is illuminated by an additional white LED and can therefore also be used in poor lighting conditions.

Transmission via USB

The data transfer of the scanned barcodes is done via the included USB cable.

Note

This scanner is intended exclusively for the output of the German keyboard.



1,5 m

Item no. 90600

EAN: 4043619906000

Country of origin: China

Package: Box

Technical details

- Connector: 1 x RJ50 jack
- Decoding chip: ARM Cortex 32 Bit
- Resolution: 752 x 480
- Trigger: presentation mode
- Reading distance: ca. 50 mm to 250 mm
- Reading accuracy: 5 mil
- Compensation light: LED white
- Sensor: CMOS image sensor
- Scan rate: up to 60 scans per second
- Surrounding brightness: max. 100000 Lux
- Input voltage: 5 V

- Current consumption:
operation: max. 100 mA
standby: max. 30 mA
 - Operating temperature: -10 °C ~ 50 °C
 - Storage temperature: -10 °C ~ 50 °C
 - Relative humidity: 5 - 95 % (non condensing)
 - Colour: black
 - Weight: ca. 173 g
 - Dimensions (LxWxH): ca. 78 x 67 x 52 mm
 - Cable length without connectors: ca. 1.5 m
 - 2.4 GHz
 - Scancodes:
Code 128
Code 39
EAN-8 / EAN-13
ISBN - 13
Data Matrix
Micro QR
PDF417
QR Code
-


System requirements

- Mac OS 12.4 or above
 - Windows 8.1/8.1-64/10/10-64/11
 - PC or laptop with a free USB Type-A port
-

Package content

- Barcode scanner
- USB data cable
- User manual

Images



Interface

connector:	1 x RJ50 jack
------------	---------------

Technical characteristics

Operating voltage:	5 V
Operating temperature:	-10 °C ~ 50 °C
Current consumption:	operation: 100 mA Standby: 30 mA
Resolution:	752 x 480 pixel
Scan rate:	60 pictures per second
Trigger:	Presentation mode
Reading distance:	50 mm - 250 mm
Sensor:	CMOS Bildsensor
Scancodes:	EAN-8 EAN-13 Standard Code 39 Code 128 PDF417 DataMatrix QR Code Micro QR Code ISBN - 13
Surrounding brightness:	100000 Lux

Physical characteristics

Weight:	173 g
Cable length:	1.5 m
Length:	78 mm
Width:	67 mm
Height:	52 mm

Colour:

black

