

# Delock Mini PCIe Card full size to 2 x Serial RS-232 D-Sub 9 pin

## Description

The Mini PCI Express card by Delock expands a PC by two external serial RS-232 ports. Different devices such as scanner, protocol converter, IoT devices etc. can be connected to this card.



**Item no. 95273**

EAN: 4043619952731

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:  
external: 2 x serial RS-232 DB9 male with nuts  
internal: 1 x Mini PCI Express, Rev. 1.1
- Chipset: Moschip MCS9901
- Form factor: Mini PCIe full size
- Data transfer rate up to 460.8 Kbps
- Compatible with 16C450 / 16C550 / 16C650 UART
- FIFO: 256 byte
- Cable length incl. connectors: ca. 30 cm

## System requirements


- Windows 8.1/8.1-64/10/10-64/11
- Motherboard with a free Mini PCIe slot with a PCIe interface

## Package content

- Mini PCIe module
- 1 x slot bracket with two serial ports
- Driver CD
- User manual

---

## Images



## General

Form factor:	Mini PCIe full size
Supported operating system:	Linux Kernel 3.7 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

## Interface

Connector 1:	1 x Mini PCI Express, Rev. 1.1
Connector 2:	2 x serial RS-232 DB9 plug

## Technical characteristics

Chipset:	ASIX MCS9904
Data transfer rate:	2 x 921,6 Kbps
FIFO:	2 x 256 Byte
Data transmission:	asynchronous full duplex Bi-directional Half duplex
UART:	16C450 / 16C550 / 16C650
Data bits:	5, 6, 7, 8
Stop bits:	1, 2

## Physical characteristics

Cable length incl. connector:	30 cm
-------------------------------	-------